



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

LOCTITE 561

SDS No. : 153640
V005.1

Revision: 14.03.2017

printing date: 22.03.2019

Replaces version from: 25.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 561

Contains:

Diamid wax mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

| | |
|--|--|
| Hazard statement: | H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects. |
| Precautionary statement: Prevention | P273 Avoid release to the environment. P280 Wear protective gloves. |
| Precautionary statement: Response | P333+P313 If skin irritation or rash occurs: Get medical advice/attention. |

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Anaerobic Sealant

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---|------------------------------------|----------------|--|
| Diamid wax mixture | 430-050-2 | 5- < 10 % | Skin Sens. 1 H317 Aquatic Chronic 2 H411 |
| Ethane-1,2-diol 107-21-1 | 203-473-3 01-2119456816-28 | 1- < 5 % | Acute Tox. 4; Oral H302 STOT RE 2; Oral H373 |
| Cumene hydroperoxide 80-15-9 | 201-254-7 | 0,1- < 1 % | Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314 |
| N,N-Diethyl-p-toluidine 613-48-9 | 210-345-0 | 0,1- < 1 % | Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Acute Tox. 3; Inhalation H331 STOT RE 2 H373 Aquatic Chronic 3 H412 |
| 1,4-Naphthalenedione 130-15-4 | 204-977-6 | 0,01- < 0,1 % | Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10 |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Sealant

| |
|---|
| SECTION 8: Exposure controls/personal protection |
|---|

8.1. Control parameters**Occupational Exposure Limits**Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | 20 | 52 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE] | | | Skin designation: | Can be absorbed through the skin. | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | | | Skin designation: | Can be absorbed through the skin. | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | 40 | 104 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL] | 40 | 104 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL] | 20 | 52 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | | | Skin designation: | Can be absorbed through the skin. | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | 25 | 125 | Time Weighted Average (TWA): | | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Cumene 98-82-8 [CUMENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative | ECLTV |

Occupational Exposure LimitsValid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | 40 | 104 | Short Term Exposure Limit (STEL): | Indicative OELV | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR] | 20 | 52 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE] | | 10 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL] | 40 | 104 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL] | 20 | 52 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Cumene 98-82-8 [ISOPROPYL BENZENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Cumene 98-82-8 [ISOPROPYL BENZENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative OELV | IR_OEL |
| Cumene 98-82-8 [ISOPROPYL BENZENE] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Cumene 98-82-8 [CUMENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative | ECLTV |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------------|-----------------|-----------------|-----|-----------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Ethane-1,2-diol 107-21-1 | aqua (freshwater) | | 10 mg/l | | | | |
| Ethane-1,2-diol 107-21-1 | aqua (marine water) | | 1 mg/l | | | | |
| Ethane-1,2-diol 107-21-1 | sediment (freshwater) | | | | 20,9 mg/kg | | |
| Ethane-1,2-diol 107-21-1 | sewage treatment plant (STP) | | 199,5 mg/l | | | | |
| Ethane-1,2-diol 107-21-1 | aqua (intermittent releases) | | 10 mg/l | | | | |
| Ethane-1,2-diol 107-21-1 | soil | | | | 1,53 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | 0,0031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Sewage treatment plant | | 0,35 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | soil | | | | 0,0029 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|---------------------------------------|---------------|-----------|---------|
| Ethane-1,2-diol 107-21-1 | Workers | dermal | Long term exposure - systemic effects | | 106 mg/kg | |
| Ethane-1,2-diol 107-21-1 | Workers | inhalation | Long term exposure - local effects | | 35 mg/m3 | |
| Ethane-1,2-diol 107-21-1 | General population | dermal | Long term exposure - systemic effects | | 53 mg/kg | |
| Ethane-1,2-diol 107-21-1 | General population | inhalation | Long term exposure - local effects | | 7 mg/m3 | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m3 | |

Biological Exposure Indices:
None**8.2. Exposure controls:**

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|------------------------------------|
| Appearance | waxy Off white |
| Odor | mild |
| Odour threshold | No data available / Not applicable |
| pH | No data available / Not applicable |
| Initial boiling point | > 150 °C (> 302 °F) |
| Flash point | Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Vapour pressure (25 °C (77 °F)) | < 13 mbar |
| Density (ρ) | 1,14 g/cm ³ |
| Bulk density | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Slight |
| Solidification temperature | No data available / Not applicable |
| Melting point | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Evaporation rate | No data available / Not applicable |
| Vapor density | No data available / Not applicable |

Oxidising properties

No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**Reaction with strong acids.
Reacts with strong oxidants.**10.2. Chemical stability**

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause irritation to respiratory system.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Prolonged or repeated contact may cause eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Acute oral toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|----------------------------------|--|-------------|-------------------------|------------------|---------|------------------|
| Ethane-1,2-diol 107-21-1 | Acute toxicity estimate (ATE) | 500 mg/kg | oral | | | Expert judgement |
| Ethane-1,2-diol 107-21-1 | LD50 | 7.712 mg/kg | | | rat | not specified |
| Cumene hydroperoxide 80-15-9 | LD50 | 550 mg/kg | oral | | rat | not specified |
| 1,4-Naphthalenedione 130-15-4 | LD50 | 190 mg/kg | oral | | rat | not specified |

Acute inhalative toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|-------|-------------------------|------------------|---------|--------|
|---------------------------------|---------------|-------|-------------------------|------------------|---------|--------|

Acute dermal toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|------------------------|-------------------------|------------------|---------|---------------|
| Ethane-1,2-diol 107-21-1 | LD50 | 10.600 mg/kg | dermal | | rabbit | not specified |
| Cumene hydroperoxide 80-15-9 | LD50 | 1.200 - 1.520 mg/kg | dermal | | | not specified |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|-------------|
| Ethane-1,2-diol 107-21-1 | not irritating | 20 h | rabbit | BASF Test |
| Cumene hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|-----------|
| Ethane-1,2-diol 107-21-1 | not irritating | | rabbit | BASF Test |

Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|---------------------------------|-----------------|------------------------------------|------------|--|
| Ethane-1,2-diol 107-21-1 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

| Hazardous components CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---------------------------------|----------|--|--|---------|---|
| Ethane-1,2-diol 107-21-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Ethane-1,2-diol 107-21-1 | negative | oral: feed | | rat | Chromosome Aberration Test |
| Cumene hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Cumene hydroperoxide 80-15-9 | negative | dermal | | mouse | not specified |

Repeated dose toxicity

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---------------------------------|--------------------|-------------------------|--|---------|--|
| Ethane-1,2-diol 107-21-1 | NOAEL=150 mg/kg | oral: feed | 16 wdaily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Cumene hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d5 d/w | rat | not specified |

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Harmful to aquatic life with long lasting effects.

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|----------------------------------|---------------|---------------|----------------------------|------------------|--------------------------------|--|
| Ethane-1,2-diol 107-21-1 | NOEC | 15.380 mg/l | Fish | 28 d | Oryzias latipes | OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study) |
| | LC50 | 72.860 mg/l | Fish | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Ethane-1,2-diol 107-21-1 | EC50 | 34.400 mg/l | Daphnia | 48 h | Ceriodaphnia sp. | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Ethane-1,2-diol 107-21-1 | EC50 | > 20.000 mg/l | Algae | | Microcystis aeruginosa | OECD Guideline 201 (Alga, Growth Inhibition Test) not specified |
| Ethane-1,2-diol 107-21-1 | EC0 | > 10.000 mg/l | Bacteria | 16 h | | |
| Ethane-1,2-diol 107-21-1 | NOEC | 8.590 mg/l | chronic Daphnia | 7 d | Ceriodaphnia sp. | OECD 211 (Daphnia magna, Reproduction Test) |
| Cumene hydroperoxide 80-15-9 | LC50 | 3,9 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 18 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Cumene hydroperoxide 80-15-9 | ErC50 | 3,1 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) not specified |
| Cumene hydroperoxide 80-15-9 | EC10 | 70 mg/l | Bacteria | 30 min | | |
| 1,4-Naphthalenedione 130-15-4 | EC50 | 0,011 mg/l | Algae | 72 h | Dunaliella bioculata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

| Hazardous components CAS-No. | Result | Route of application | Degradability | Method |
|---------------------------------|--------|-------------------------|---------------|--------|
| | | | | |

| | | | | |
|----------------------------------|-----------------------|---------|-----------|---|
| Ethane-1,2-diol 107-21-1 | readily biodegradable | aerobic | 83 - 96 % | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Cumene hydroperoxide 80-15-9 | | no data | 0 % | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| 1,4-Naphthalenedione 130-15-4 | | no data | 0 - 60 % | OECD 301 A - F |

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

| Hazardous components CAS-No. | LogPow | Bioconcentration factor (BCF) | Exposure time | Species | Temperature | Method |
|----------------------------------|--------|----------------------------------|------------------|-------------|-------------|---|
| Ethane-1,2-diol 107-21-1 | -1,36 | | | | | not specified |
| Cumene hydroperoxide 80-15-9 | | 9,1 | | calculation | | OECD Guideline 305 (Bioconcentration: Flow- through Fish Test) not specified |
| Cumene hydroperoxide 80-15-9 | 2,16 | | | | | not specified |
| 1,4-Naphthalenedione 130-15-4 | 1,71 | | | | | not specified |

12.5. Results of PBT and vPvB assessment

| Hazardous components CAS-No. | PBT/vPvB |
|---------------------------------|---|
| Ethane-1,2-diol 107-21-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Cumene hydroperoxide 80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H242 Heating may cause a fire.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.